



The
**Patent
Office**

PIB34169
U.S.A #4

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP9 1RH

10518 U.S. PTO

09/118572



07/17/98

**CERTIFIED COPY OF
PRIORITY DOCUMENT**

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated

26th November 1997.

~~insert here blank (uspto)~~

This Page Blank (uspto)

Request for grant of a patent

(See notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

£25

18JUL97 E2897 The Patent Office
P01/7700 25.00 - 9715005.6

Cardiff Road
Newport
Gwent NP9 1RH

1. Your reference

PHB 34169

THE PATENT OFFICE

D

2. Patent application number

(The Patent Office will fill in this part)

9715005.6

17 JUL 1997

RULE 97

RECEIVED BY POST

3. Full name, address and postcode of the or of each applicant (underline all surnames)

PHILIPS ELECTRONICS N.V.
GROENEWOUDSEWEG 1
5621 BA EINDHOVEN
THE NETHERLANDS
06828487001

17 JUL 1997

Patents ADP Number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

THE NETHERLANDS

4. Title of the invention

GRAPHIC IMAGE TEXTURE GENERATION

5. Name of your agent (if you have one)

ANDREW GORDON WHITE

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Philips Electronics
Patents & Trade Marks Department
Cross Oak Lane
Redhill
Surrey RH1 5HA
974790007

Patents ADP number (if you know it)

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority Application number
(if you know it)

Date of filing
(day/month/year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day/month/year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer "Yes" if:

YES

a) any applicant named in part 3 is not an inventor, or

b) there is an inventor who is not named as an applicant, or

c) any named applicant is a corporate body.

See note (d))

9. Enter the number of sheets for any of the following items you are filing with this form.
Do not count copies of the same document.

Continuation sheets of this form

Description	12 (x2)
Claims(s)	3 (x2)
Abstract	1 (x2)
Drawings	4 (x2)

10. If you are also filing any of the following, state how many against each item:

Priority Documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and search (*Patents Form 9/77*)


Request for substantive examination (*Patents Form 10/77*)

Any other documents
(Please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature



Date

16 July, 1997

12. Name and daytime telephone number of person to contact in the United Kingdom

01293 815299 (Andrew G White)

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- a) *If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.*
- b) *Write your answers in capital letters using black ink or you may type them.*
- c) *If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.*
- d) *If you have answered "Yes" Patents Form 7/77 will need to be filed.*
- e) *Once you have filled in the form you must remember to sign and date it.*
- f) *For details of the fee and ways to pay please contact the Patent Office.*

DESCRIPTION

GRAPHIC IMAGE TEXTURE GENERATION

5 The present invention relates to image processing and in particular to means for texture mapping in the rendering of two dimensional pixel images, where those images are made up of a number of polygons defined in three-dimensional (object) space and projected into two-dimensional (screen) space, and pixel texture values (texels) from a two dimensional texture map are mapped onto pixel positions within the projected two dimensional polygons.

 The process of texture mapping is well known, in essence comprising the step of wrapping a two-dimensional picture or texture over a geometric surface in order to give a greater degree of realism and often a reduction in the geometric complexity of the object. Basic texture mapping techniques are described for example in "Computer Graphics: Principles and Practice" by 15 Foley, van Dam, Feiner and Hughes, published by Addison Wesley 1990, ISBN 0-201-12110-7, at pages 741-744.

 An increasingly common use for texture mapping of polygons is in the generation of so-called virtual environments which a user is then enabled to navigate or even interact with, for example in a flight simulator or virtual reality and games applications. Whilst generally hosted on a single system, these generated virtual environments are not limited to a single user and, with the increase in communications via local or large area data networks, a single virtual environment may be visited simultaneously by users from different countries or continents. As with all such data networks, however, there is a limit to the available bandwidth which raises the need to find a balance between the frequency at which updated images of the virtual environment may be transmitted across the network and the level of detail that may be represented.

 The problem may be reduced when the format of data storage and

representation for such virtual environments is at least partially standardised, allowing for greater interchange between systems of different manufacturers and simplification of standard commands, as well as a reduction in the necessity for individually tailored translation utilities. With at least partial
5 standardisation, the necessary configuration of a browser for accessing such data, whether in a hardware or software implementation or a mixture of the two, becomes simpler.

A notable example of standardisation in the field of data defining virtual environments is the so-called Virtual Reality Modelling Language (VRML) as
10 described, for example, in the VRML standard, version 2.0, issued as ISO/IEC WD14772 on 4th August 1996. VRML is a file format for describing interactive three-dimensional objects and worlds to be experienced on the Internet/World Wide Web and it is generally analogous to the way HTML (HyperText Markup Language) is used to describe documents for transmission over the Internet.
15 In order to simplify the specification of how objects appear within a virtual environment, it is a known technique in formats such as VRML to restrict such objects to constructions from a limited set of "building blocks" such as rods, cones and cubes, which may be simply specified in relatively few parameters.

In an Internet White Paper issued by S3 Incorporated in January 1997,
20 entitled "Delivering Compelling 3D Content on the Web" it was proposed to extend this standardisation to textures and, in order to reduce the volume of data transmitted per scene, to provide users with a local library of the standard textures in the form of a collection of texture maps to be held on the users hard drive: operationally it was suggested that the users system would first check
25 the local hard drive for a specified texture before calling for it to be transmitted from the virtual environment host.

Whilst maintaining a local store of textures does greatly reduce the volume of data sent via data network, it does generate its own problems. Apart from the expected difficulties of persuading different system manufacturers to
30 agree on a standardised texture set, the principle problem is the amount of space on a users hard disk that will be taken up if the set contains many

different textures. This problem is compounded by the need to hold each texture at at least two different resolutions to enable interpolation and extrapolation techniques to be used to create textures at desired resolution levels. Furthermore, whilst the volume of data network traffic is reduced, there is an increase within the users system, between a graphics engine and the hard disk.

It is therefore an object of the present invention to reduce the volume of data required to be stored by a users system without generating a corresponding increase in external data traffic.

In accordance with a first aspect of the present invention there is provided an apparatus for texture mapping in a computer graphics system, using a predetermined set of standardised textures, the apparatus having an input to receive data identifying one of the set of standardised textures, and means for processing the data to generate output texels of the identified texture; characterised in that each texture of the standardised set is a procedural texture, the input identifying data comprises one or a sequence of program commands the execution of which will result in the generation of a respective procedural texture, with the means for processing data comprising a processor operable to implement all such input program commands or sequences of input programme commands as required to generate the procedural textures of the standardised set.

By using a standardised set of procedural textures (texture patterns which may be generated from a specifying descriptor or algorithm, such as chess boards, woodgrain or marbling), the need to give over areas of local storage to texture maps is avoided as the texture can be generated as required. Suitably, the apparatus has at least one further input for one or more predetermined classes of numerical parameter, with the processor being arranged to generate procedural textures with reference to the or each numerical parameter value received. Such a predetermined class of numerical parameter may suitably comprise a scale factor, or the scale factor may be

input in a different form, with the processor then being arranged to generate a procedural texture at a resolution determined by a received scale factor. In terms of a two-dimensional image composed from polygons projected from three-dimensional object space, this scale factor will directly relate the depth and orientation of the polygon surface to be textured with the texture resolution to be applied. With such parameterisation of the predetermined procedural texture set, the requirement to specify texture at different levels of resolution is avoided, further reducing the volume of data involved.

In a preferred embodiment, the processor is operable to implement only such input program commands or sequences of input programme commands as required to generate those procedural textures of the standardised set. This places a finite limit on the required capability of the processor leading to faster operation and allowing the apparatus to be implemented as a single semiconductor chip.

In a modified embodiment, the apparatus may further comprise a cache memory coupled with the processor, with the processor being configured to generate said procedural textures as texture maps within said cache. Such an embodiment suitably further comprises an input to receive a scale factor, and an interpolator to generate output texels from texture map entries in the cache at a resolution determined by the received scale factor. As with the first embodiment, this modified embodiment may suitably be provided on a semiconductor chip, with the processor, cache and interpolator on a common substrate. Although not as flexible or fast as the direct texel generation of the first embodiment, this modified embodiment with cache is substantially faster than the prior art technique of storing the predetermined textures as a series of texture maps on a users hard disk and then reading the required texel values.

Also in accordance with the present invention there is provided a computer graphics system including either the first or modified embodiments of texture mapping apparatus described above, together with a source of three-dimensional polygon data, a geometry processor coupled to receive said

5 polygon data and arranged to generate a two-dimensional representation of said polygons, a source of program commands coupled to the input of the texture mapping apparatus and specifying textures to be applied to respective ones of said polygons, and rendering means coupled to receive the outputs of the geometry processor and texture mapping apparatus and arranged to generate an output image of said polygons with texture applied.

10 In such a computer graphics system, the sources of polygon data and program commands may comprise an interface to a data network (such as the Internet) to which are coupled remote sources of such polygon data and program commands, the interface being coupled with a memory holding a store of network addresses for such remote sources and being operable to format and transmit messages to such addresses calling for the polygon data and program commands. In such an arrangement, the use of a standardised set of procedural textures provides a notable speed improvement due to the reduced volume of data transmitted in comparison with a full texture map: due to the standardisation of the set, only a short identifier may be required in the request for texture, and its transmitted form as a sequence of program commands will be of smaller volume than sending a full texture map in encoded form. In this networked embodiment, for reasons of flexibility, the program commands are liable to be transmitted over the network in a virtual machine code and the system accordingly further comprises means for conversion of the same to a local machine code supported by the processor.

25 Preferred embodiments of the present invention will now be described, by way of example only, with reference to the accompanying drawings, in which:

Figure 1 is a block schematic diagram of an image processing system embodying the present invention;

30 Figure 2 is a simplified flow chart illustrating data acquisition procedure of the system of Figure 1;

Figures 3 and 4 represent two different configurations of texture data

processing circuit for use in the system of Figure 1; and

Figure 5 is a flow chart illustrating implementation of a processing capability check applied to the system of Figure 1.

5 In the following examples, a system supporting the above-mentioned VRML standard for describing virtual environments and embodying the present invention for texture mapping in the generation of two-dimensional images of such environments will be described. It will be recognised, however, that conformance with the VRML standard is neither an essential nor a limiting
10 feature of the present invention.

 Figure 1 is a block schematic diagram of a user apparatus, such as a personal computer (PC) 10, for accessing a virtual environment via connection to a data network 12 - for example the Internet/World Wide Web, with the virtual environment being provided by a remote service provider 14. The data
15 16 defining the appearance, structure and behaviour of the virtual environment in conformance with the VRML standard is accessed by the user sending a request message to the service provider VRML store, as identified by a unique URL (uniform resource locator). Also provided by the service provider is a source 18 of control and operational instructions for implementing operational
20 features of the virtual environment. These instructions, preferably as segments of a virtual machine code (such as the Java ® virtual machine language developed by Sun Microsystems Inc) for general system flexibility, are accessed by the users system via a further URL, as will be described below.

 The users system 10 comprises a main processor 20 coupled via
25 address and data bus 22 to a random-access memory (RAM) 24, such as a hard disk, and read-only memory (ROM) 26. Also connected via the bus 22 are one or more user input devices 28, such as a keyboard and mouse or joystick, and an interface 30 to the network 12. The users system is configured, via an operating program loaded from ROM 26, as a network
30 browser with the network interface configured according to the type of data transfer supported by the users system: for a home user, the network link is

likely to be via telephone line and accordingly the interface will incorporate a modem, controlled from the main processor 20.

Further details of the above described features of the users system will be familiar to the skilled practitioner and will not be further discussed herein, unless relevant to or illustrative of the operation of the present invention. It will be understood that the user apparatus need not be a PC; consumer systems specialising in network access/browsing (but otherwise of limited capability) such as the Philips Magnavox WebTV® and similar systems may embody the present invention.

The generation of images of the virtual environment from the data obtained via the network 12 is handled by a graphics processor 32 and texture management stage 34, both of which are coupled to receive input data via the address and data bus 22. The texture management stage 34, generating texels using parameterised procedural texture specifications, supplies the texture to be applied by the graphics processor 32 to the polygonal image primitives making up the image of the virtual environment. The generated images, assembled in a frame buffer 36, are finally output to a display device 38, such as a computer monitor.

The general procedure implemented by the system of Figure 1 in obtaining data from the service provider and generating images of the virtual environment will now be described with reference to the flow chart of Figure 2. As indicated previously, the first step 201 is for the system to contact the service provider and request downloading of the data defining the virtual environment in accordance with the VRML specification. Nested within the VRML data supplied by the service provider will be pointers to further locations (in the form of further URLs) from which the required specification of the procedural data required for rendering the VRML scene may be obtained. Consequently, the next step 202 of the procedure is to identify and extract these texture URLs from the received VRML data stream.

Having obtained the texture URL, or more preferably a sequence of URLs identifying a preferred and a number of alternative sources for the

information, the user's system (at step 203) will sequentially attempt to contact the URLs listed to obtain the procedural texture data until it is successful. It should be noted that the way in which the user's system is configured as a browser differs slightly with respect to conventional web browsers in that on contacting a site identified by URL to obtain texture data, a conventional browser would be seeking to obtain a texture map or image whereas the browser embodying the present invention will be requesting the supply of machine code segments held at these sites. These machine code segments will suitably be in a machine-independent form such as the above mentioned Java® virtual code.

Having successfully contacted a site capable of supplying the machine-independent code segments specifying the required procedural texture or textures, the user's system receives from this source a short code segment (at step 204) referred to as a code skeleton. The function of the code skeleton is to cause the user's system to request from the source the texture specifying data in a form most suited to the texture data processing capability of the user's system. A more detailed description of the implementation of this skeleton will be given hereinafter with regard to the flow chart of Figure 5.

Continuing with Figure 2, having obtained the procedural texture specifications from the remote source, and translated them as necessary from the machine-independent code form to the local machine code of the user's system, the generation of the textured image commences at step 205 with the execution of the procedural textural specifications (via texture generation stage 34; Figure 1) such as to obtain, at step 206, the required texels for mapping at the resolution required. While this is occurring, the VRML data received is parsed and processed, at step 207 (in graphics engine 32; Figure 1), to generate a model of the virtual environment and its behaviour, including identifying the various surfaces to be textured and their associated scale and/or depth value, such as to determine the required resolution for the texture pattern to be mapped. The final stage, at step 208, combines the generated texture and polygonal image data defining the virtual environment and rendering a two-

dimensional image thereof into the frame buffer (36; Figure 1) for subsequent display.

Figures 3 and 4 illustrate two alternative configurations for the texture generation circuit 34 of Figure 1 each of which may suitably be implemented as a single semiconductor chip device. In the first embodiment, of Figure 3, the bulk of device comprises a limited instruction set processor 40 having the capability to run the machine code segments that specify the various procedural textures of a predetermined standard set, but with little other capability such as to maximise the efficiency in generation of the procedural textures. In the arrangement shown, a small non-volatile memory 42 is provided to hold the limited operating system for the processor 40 for fast initialisation of the texture processor 34 on boot-up or initialisation of the system. In an alternative arrangement (not shown), memory 42 may be omitted, with the processor operating system being loaded up from system ROM (26; Figure 1).

In addition to an input 44 for the machine code segments (from bus 22; Figure 1) the texture processor of Figure 3 has additional inputs 46 for a number of parameters including a depth value. This depth value represents the apparent depth, and suitably also orientation, of the polygonal surface onto which the texture to be generated is to be mapped. This depth value will provide an indication of the polygon "footprint" when translated to two-dimensional screen space and hence will have a direct bearing on the resolution at which the texture is to be generated, such that the output texels generated (on line 48) will not need scaling before being mapped directly onto a polygonal surface.

An alternative configuration for the texture processor 34' is shown in Figure 4. Here it is assumed that the processor 50, whilst still having an operating system capability to handle all procedural textures specified in the above mentioned standardised set, is a more general device. Here, rather than generating texels to order at a given scale, the processor generates a texture map (or map segment) into an associated cache memory 52 suitably at two or

more levels of resolution. From these different levels of resolution, interpolator stage 54, in response to receipt of the polygon depth signal generates texels for display at the desired resolution. Whilst the configuration of Figure 4 is not as efficient as that of Figure 3, due to the lack of a specialised processor and the need to generate texture maps and then interpolate, it is a much faster option than, say, calling for texture maps to be downloaded from system storage (such as the user system hard disk) due to the proximity of processor 50 and cache 52.

Turning now to the flow chart of Figure 5, this schematically represents both the operational features and results of implementation of the skeleton code sent by a source of procedural texture specification codes to identify the texture processing capability of the requesting system. The procedure begins at step 501 with a direction for the user's system to identify its texture processing capability, preferably by use of short code words indicating predetermined types. The first check, at step 502, is whether the processor is a limited instruction set processor dedicated to the standardised set of procedural textures, as with the processor of Figure 3. If the user system does have such a texture processor, the user system can proceed to obtain the procedural texture codes and any associated scaling factors (at step 503) and subsequently (at step 504) generate on demand texels of the pattern required and to the scale desired.

If the check at step 502 is negative, that is to say the texture processor is not based on a limited instruction set processor, the next check at step 505 is to whether the texture processor has an onboard cache memory, as in the embodiment of Figure 4. If this is the case, then, at step 506, the machine code segments specifying the procedural texture may again be obtained and implemented by the processor (50; Figure 4) such as to generate one or more texture maps into the cache at step 507. Having determined (at step 508) the depth of the polygon surface to be textured with reference to a specified texture resolution for that polygon, the extent to which the texture for the polygon needs to be scaled up or down may be determined (at step 508). From the

data in the cache an interpolator may then generate texture to the required resolution (step 509).

If the checks of both steps 502 and 505 are negative, the next step (510) is to determine whether the texture handling circuitry of the user system has
5 any capacity for handling of procedural textures (perhaps implemented in the main system CPU rather than a dedicated texture processor). If there is a procedural capacity, the system will again proceed to obtain the code segments specifying the textures to be mapped at step 511 and to generate one or more resolutions of texture map at step 512. In this instance, without benefit of an
10 on-chip cache the more lengthy process of storing the generated texture maps in RAM has to be gone through (at step 513). In order to generate texels for mapping, data from the generated and stored texture maps must be read from the RAM (step 514) and interpolated as required (step 515) in order to generate the necessary texels at the correct resolution.

15 The remaining stages of the procedure are in the form of a fail-safe measure if checks 502, 505 and 510 are negative (that is to say the user system has no capability for procedural texture in any form). In the absence of procedural texture capability, a check is made (step 516) to determine whether the user system has any capability for the storage of texture maps
20 and, if so, these will be called (step 517) from their remote source and downloaded via the data network to be stored in the system RAM on receipt.

The final step, should even the check of step 516 prove negative, is to use a single texture value for all surfaces to be textured (step 518): for example, all surfaces to be textured may appear as coloured purple.

25

From reading the present disclosure, other modifications will be apparent to persons skilled in the art. Such modifications may involve other features which are already known in the design, manufacture and use of image processing apparatus and devices and component parts thereof and which may
30 be used instead of or in addition to features already described herein. Although claims have been formulated in this application to particular combinations of

features, it should be understood that the scope of the disclosure of the present application also includes any novel feature or novel combination of features disclosed herein either explicitly or implicitly or any generalisation thereof, whether or not it relates to the same invention as presently claimed in any claim and whether or not it mitigates any or all of the same technical problems as does the present invention. The applicants hereby give notice that new claims may be formulated to such features and/or combinations of such features during the prosecution of the present application or of any further application derived therefrom.

CLAIMS

1. Apparatus for texture mapping in a computer graphics system, using a predetermined set of standardised textures, the apparatus having an input to receive data identifying one of the set of standardised textures, and means for processing the data to generate output texels of the identified texture; characterised in that each texture of the standardised set is a procedural texture, the input identifying data comprises one or a sequence of program commands the execution of which will result in the generation of a respective procedural texture, with the means for processing data comprising a processor operable to implement all such input program commands or sequences of input programme commands as required to generate the procedural textures of the standardised set.

2. Apparatus as claimed in Claim 1, having at least one further input for one or more predetermined classes of numerical parameter, with the processor being arranged to generate procedural textures with reference to the or each numerical parameter value received.

3. Apparatus as claimed in Claim 1 or Claim 2, having at least one further input for a scale factor, with the processor being arranged to generate a procedural texture at a resolution determined by a received scale factor.

4. Apparatus as claimed in any of Claims 1 to 3, wherein the processor is operable to implement only such input program commands or sequences of input programme commands as required to generate those procedural textures of the standardised set.

5. Apparatus as claimed in Claim 1, further comprising a cache memory coupled with the processor, with the processor being configured to generate said procedural textures as texture maps within said cache.

6. Apparatus as claimed in Claim 5, further comprising an input to receive a scale factor, and an interpolator to generate output texels from texture map entries in the cache at a resolution determined by the received scale factor.

5

7. A semiconductor chip comprising a texture mapping apparatus as claimed in Claim 4 on a single substrate.

10

8. A semiconductor chip comprising a texture mapping apparatus as claimed in Claim 6, with the processor, cache and interpolator on a common substrate.

15

9. A computer graphics system including an apparatus as claimed in any of Claims 1 to 6, together with a source of three-dimensional polygon data, a geometry processor coupled to receive said polygon data and arranged to generate a two-dimensional representation of said polygons, a source of program commands coupled to the input of the texture mapping apparatus and specifying textures to be applied to respective ones of said polygons, and rendering means coupled to receive the outputs of the geometry processor and texture mapping apparatus and arranged to generate an output image of said polygons with texture applied.

20

25

10. A computer graphics system as claimed in Claim 9, wherein the sources of polygon data and program commands comprise an interface to a data network to which are coupled remote sources of such polygon data and program commands, the interface being coupled with a memory holding a store of network addresses for such remote sources and being operable to format and transmit messages to such addresses calling for the polygon data and program commands.

30

11. A computer graphics system as claimed in Claim 10, wherein said

program commands are transmitted over the network in virtual machine code and the system further comprises means for conversion of the same to a local machine code supported by the processor.

- 5 12. Apparatus for texture mapping in a computer graphics system substantially as hereinbefore described with reference to the accompanying drawings.

ABSTRACT

GRAPHIC IMAGE TEXTURE GENERATION

5 An apparatus (34) for texture mapping in a computer graphics system,
using a predetermined set of standardised textures. Each texture of the
standardised set is a procedural texture, and is supplied to the apparatus (34)
as one or a sequence of program commands (44) the execution of which will
result in the generation of the respective procedural texture. In a preferred
10 embodiment, the means for processing the program commands (4) comprises
a processor operable to implement only those input program commands or
sequences of input programme commands as are required to generate the
procedural textures of the standardised set.

15

[Figure 3]

1/4







FIG. 1

PHB 34169


This Page Blank (uspto)



This Page Blank (uspto)

FIG. 3FIG. 4

This Page Blank (uspto)

FIG. 5

This Page Blank (uspto)